



РӨСӘЙ ФЕДЕРАЦИЯҢЫ
БАШКОРТОСТАН РЕСПУБЛИКАҢЫ
"САЛАУАТБЫЯЛА"
АКЦИОНЕРЗАР ЙӘМГИӘТЕ
453253, РФ, РБ
Салауат к. Индустриаль ур., 18
тел.: (3476)37-72-09, секретарь 37-71-55,
коммерция хеҙмәте 37-71-20,
www.salstek.ru



104213/A/0001/UK/RUS
Система менеджмента
качества сертифицирована
на соответствие требованиям
ISO 9001:2015



104213/B/0001/SM/RUS
Система менеджмента
качества сертифицирована
на соответствие требованиям
IATF 16949:2016

РОССИЙСКАЯ ФЕДЕРАЦИЯ
РЕСПУБЛИКА БАШКОРТОСТАН
АКЦИОНЕРНОЕ ОБЩЕСТВО
«САЛАВАТСТЕКЛО»
453253, РФ, РБ
г. Салават, ул. Индустриальная, 18
тел.: (3476) 37-72-09, секретарь 37-71-55,
коммерческая служба 37-71-20,
www.salstek.ru

ИНН 0266004050, КПП 026601001, ОКПО 04616815, ОГРН 1020201995043, р/с 40702810806404000298, Башкирское отделение № 8598 ПАО Сбербанк, БИК 048073601, к/с № 30101810300000000601



DECLARATION OF CONFORMITY No. 027-2021/11

Unique identification code of the product-type:	Glass with multifunctional coating (class C)	
Intended use	Buildings and construction works	
Manufacturer:	“Salavatsteklo” JSC Industrialnaya str. 18, Salavat, Republic of Bashkortostan, Russia 453253	
Harmonised standart	EN 1096-4 Glass in building – Coated glass.– Part 4. Product standard	
AVCP system:	3	
Notified body:	IKATES, s.r.o. - Laboratory for glass and building products testing Testing laboratory No 1139	
Test reports	No.: 1394-CPR-143B/2018	No.: 1394-CPR-143B/2021

Characteristics:	MF NEUTRAL		MultiComfort ⁰ Blue 37/28		MultiComfort ⁰ Neutral 66/43
	4 mm	6 mm	4 mm	6 mm	4 mm
Resistance to fire	NPD	NPD	NPD	NPD	NPD
Reaction to fire	A1*	A1*	A1*	A1*	A1*
External fire behavior	NPD	NPD	NPD	NPD	NPD
Bullet resistance	NPD	NPD	NPD	NPD	NPD
Explosion resistance	NPD	NPD	NPD	NPD	NPD
Burglar resistance	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials	40K				
Resistance against wind, snow, permanent load and/or imposed loads	45·10 ⁶ Pa				
Direct airborne sound reduction	NPD	NPD	NPD	NPD	NPD
Thermal properties	NPD	NPD	NPD	NPD	NPD
Radiation properties:					
Light transmission coefficient (τ_v)	0,69	0,69	0,39	0,39	0,69
Light transmission and reflection (ρ_v / ρ'_v)	0,17 / 0,22	0,17 / 0,21	0,11 / 0,30	0,11 / 0,29	0,20 / 0,24
Solar factor (g)	0,48	0,47	0,38	0,37	0,49
Normal emissivity ϵ_n / corrected emissivity ϵ (emissivity value)	0,030 / 0,037		0,034 / 0,042		0,028 / 0,033
UF resistance	PASS	PASS	PASS	PASS	PASS

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Salavat, Russia
2021/11/25



Agureev S.A. General Director of
“SALAVATSTEKLO” JSC