



РОССИЙСКАЯ ФЕДЕРАЦИЯ  
 БАШКОРТОСТАН РЕСПУБЛИКАСЫ  
 "САЛАУАТБЫЛА"  
 АКЦИОНЕРЗАР ЙЭМГНЭТЕ  
 453253, РФ, РБ  
 Салауат к. Индустриаль ур. 18  
 тел.: (3476)37-72-09, секретарь 37-71-55,  
 коммерция хеҙмәте 37-71-20,  
 www.salstek.ru



104213/A/0001/UK/RUS  
 Система менеджмента  
 качества сертифицирована  
 на соответствие требованиям  
 ISO 9001:2015



104213/B/0001/SM/RUS  
 Система менеджмента  
 качества сертифицирована  
 на соответствие требованиям  
 IATF 16949:2016

РОССИЙСКАЯ ФЕДЕРАЦИЯ  
 РЕСПУБЛИКА БАШКОРТОСТАН  
 АКЦИОНЕРНОЕ ОБЩЕСТВО  
 «САЛАВАТСТЕКЛО»  
 453253, РФ, РБ  
 г. Салават, ул. Индустриальная, 18  
 тел.: (3476) 37-72-09, секретарь 37-71-55,  
 коммерческая служба 37-71-20,  
 www.salstek.ru

ИНН 0266004050, КПП 026601001, ОКПО 04616815, ОГРН 1020201995043, р/с 40702810806404000298, Башкирское отделение № 8598 ПАО Сбербанк, БИК 048073601, к/с № 30101810300000000601



## DECLARATION OF CONFORMITY No. 029-2021/11

Unique identification code of the product-type:	<b>Glass with solar control coating (class B)</b>	
Intended use	Buildings and construction works	
Manufacturer:	<b>"Salavattsteklo" JSC          Industrialnaya str. 18, Salavat, Republic of Bashkortostan, Russia 453253</b>	
Harmonised standart	EN 1096-4 Glass in building – Coated glass. – Part 4. Product standard	
Harmonised standart	3	
Notified body:	IKATES, s.r.o. - Laboratory for glass and building products testing Testing laboratory No 1139	
Test reports	No.: 1394-CPR-143A/2018	No.: 1394-CPR-150A/2021

Characteristics:	Comfort <sup>o</sup> blue 20		Comfort <sup>o</sup> silver-grey 40		Comfort <sup>o</sup> gold 20	Comfort <sup>o</sup> grey 20	Comfort <sup>o</sup> elit+
	4 mm	6 mm	4 mm	6 mm	4 mm	4 mm	4 mm
Resistance to fire	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	A1*	A1*	A1*	A1*	A1*	A1*	A1*
External fire behavior	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Bullet resistance	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials	40K						
Resistance against wind, snow, permanent load and/or imposed loads	45·10 <sup>6</sup> Pa						
Direct airborne sound reduction	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Thermal properties	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Condensation water resistance	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Acid resistance	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Neutral salt spray resistance	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Abrasion resistance	PASS	PASS	PASS	PASS	PASS	PASS	PASS
<b>Radiation properties:</b>							
Light transmission coefficient ( $\tau_v$ )	0,20	0,20	0,40	0,39	0,21	0,20	0,66
Light transmission and reflection ( $\rho_v / \rho'_v$ )	0,37 / 0,21		0,13 / 0,24		0,24 / 0,36	0,32 / 0,29	0,34 / 0,33
Solar factor (g)	0,24	0,23	0,41	0,41	0,35	0,30	0,69

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Salavat, Russia  
 2021/11/25



Agureev S.A. General Director of  
 "SAVATSTEKLO" JSC