



РЭСЭЙ ФЕДЕРАЦИЯҢЫ
БАШКОРТОСТАН РЕСПУБЛИКАҢЫ
“САЛАУАТБЫЯЛА”
АКЦИОНЕР ЗАР ЙӘМФИӨТЕ
453253, РФ, РБ
Салауат к., Индустриаль ур., 18
тел.: (3476)33-46-25, секретарь 33-52-51
коммерция хезмәте 33-49-50, 33-06-63
факс (3476) 33-52-70 www.salstek.ru



104213/A/0001/UK/RUS
Система менеджмента
качества сертифицирована
на соответствие требованиям
ISO 9001:2015



104213/B/0001/SM/RUS
Система менеджмента
качества сертифицирована
на соответствие требованиям
IATF 16949:2016

РОССИЙСКАЯ ФЕДЕРАЦИЯ
РЕСПУБЛИКА БАШКОРТОСТАН
АКЦИОНЕРНОЕ ОБЩЕСТВО
«САЛАВАТСТЕКЛО»
453253, РФ, РБ
г. Салават, ул. Индустриальная, 18
тел.: (3476) 33-46-25, секретарь 33-52-51
коммерческая служба 33-49-50, 33-06-63
факс (3476) 33-52-70 www.salstek.ru

ИНН 0266004050, КПП 026601001, ОКПО 04616815, ОГРН 1020201995043, р/с 40702810806404000298, Башкирское отделение № 8598 ПАО Сбербанк, БИК 048073601, к/с № 30101810300000000601



DECLARATION OF CONFORMITY No. 009-2019/12

Unique identification code of the product-type:	Glass with multifunctional coating (class C)
Intended use	Buildings and construction works
Manufacturer:	“Salavatsteklo” JSC Industrialnaya str. 18, Salavat, Republic of Bashkortostan, Russia 453253
Authorised representative:	SOKOL TRANS GROUP SP z o.o. Polska, Lublin, 20-026, Fryderyka Chopina, 15/15A, Phone No: +48884290051, Email: sokoltransgroup@gmail.com
Harmonised standart	EN 1096-4 Glass in building – Coated glass.– Part 4. Product standard
AVCP system:	3
Notified body:	IKATES, s.r.o. - Laboratory for glass and building products testing Testing laboratory No 1139. Test report No.: 1394-CPR-143B/2018

Characteristics:	MF NEUTRAL		MultiComfort ⁰ blue 40/38	
	4 MM	6 MM	4 MM	6 MM
Resistance to fire	NPD	NPD	NPD	NPD
Reaction to fire	A1*	A1*	A1*	A1*
External fire behavior	NPD	NPD	NPD	NPD
Bullet resistance	NPD	NPD	NPD	NPD
Explosion resistance	NPD	NPD	NPD	NPD
Burglar resistance	NPD	NPD	NPD	NPD
Pendulum body impact resistance	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials	40K			
Resistance against wind, snow, permanent load and/or imposed loads	45·10 ⁶ Pa			
Direct airborne sound reduction	NPD	NPD	NPD	NPD
Thermal properties	NPD	NPD	NPD	NPD
Radiation properties:				
Light transmission coefficient (τ)	0,69	0,69	0,39	0,39
Light transmission and reflection (ρ_V / ρ'_V)	0,17 / 0,22	0,17 / 0,21	0,11 / 0,30	0,11 / 0,29
Solar factor (g)	0,48	0,47	0,38	0,37
Normal emissivity ϵ_n /corrected emissivity ϵ (emissivity value)	0,030 / 0,037		0,034 / 0,042	
UF resistance	PASS	PASS	PASS	PASS

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Salavat
Russia
2019/12/13



Agureev S.A.
General Director of
“SALAVATSTEKLO” JSC