



РЭСЭЙ ФЕДЕРАЦИЯҒЫ  
БАШКОРТОСТАН РЕСПУБЛИКАҒЫ  
“САЛАУАТБЫЯЛА”  
АКЦИОНЕРҒАР ЙӘМӘПӘТЕ  
453253, РФ, РБ

Салауат к., Индустриаль ур., 18  
тел.: (3476)33-46-25, секретарь 33-52-51  
коммерция хезмәте 33-49-50, 33-06-63  
факс (3476) 33-52-70 www.salstek.ru



104213/A/0001/UK/RUS  
Система менеджмента  
качества сертифицирована  
на соответствие требованиям  
ISO 9001:2015



104213/B/0001/SM/RUS  
Система менеджмента  
качества сертифицирована  
на соответствие требованиям  
IATF 16949:2016

РОССИЙСКАЯ ФЕДЕРАЦИЯ  
РЕСПУБЛИКА БАШКОРТОСТАН  
АКЦИОНЕРНОЕ ОБЩЕСТВО  
«САЛАВАТСТЕКЛО»  
453253, РФ, РБ

г. Салават, ул. Индустриальная, 18  
тел.: (3476) 33-46-25, секретарь 33-52-51  
коммерческая служба 33-49-50, 33-06-63  
факс (3476) 33-52-70 www.salstek.ru

ИНН 0266004050, КПП 026601001, ОКПО 04616815, ОГРН 1020201995043, р/с 40702810806404000298, Башкирское отделение № 8598 ПАО Сбербанк, БИК 048073601, к/с № 30101810300000000601



## DECLARATION OF CONFORMITY №. 007-2019/05

Unique identification code of the product-type:	<b>Thermally toughened float glass</b>
Intended use	Buildings and construction works
Manufacturer:	<b>“Salavatsteklo” JSC Industrialnaya str. 18, Salavat, Republic of Bachkortostan, Russia 453253</b>
Authorised representative:	<b>SOKOL TRANS GROUP SP z o.o. Polska, Lublin, 20-026, Fryderyka Chopina, 15/15A Phone No: +48884290051, Email: sokoltransgroup@gmail.com</b>
Harmonised standart	EN 12150-2 Glass in building - Thermally toughened soda lime silicaty safety glass– Part 2: Evaluation of conformity/ Product standard
AVCP system:	3
Notified body:	IKATES, s.r.o. - Laboratory for glass and building products testing Testing laboratory No 1394 Test report No.: 24 / 2019

Characteristics:	Performance
	4 mm
Resistance to fire	NPD
Reaction to fire	A1*
External fire behavior	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature changes and temperature differentials	200K
Resistance against wind, snow, permanent load and/or imposed loads (bending strength test)	4 mm
Direct airborne sound reduction	NPD
Thermal properties	NPD
Fragmentation test	PASS
<b>Radiation properties:</b>	
Light transmission and reflection	PASS
Solar energy characteristics	PASS

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Salsvat  
Russia  
2019/05/20

