



РӨСӘЙ ФЕДЕРАЦИЯҢЫ
БАШКОРТОСТАН РЕСПУБЛИКАҢЫ
“САЛАУАТБЫЯЛА”
АКЦИОНЕРЗАР ЙӨМФИӨТЕ
453253, РФ, РБ

Салауат к., Индустриаль ур., 18
тел.: (3476)33-46-25, секретарь 33-52-51
коммерция хезмәте 33-49-50, 33-06-63
факс (3476) 33-52-70 www.salstek.ru



104213/A/0001/UK/RUS

Система менеджмента
качества сертифицирована
на соответствие требованиям
ISO 9001:2015



104213/B/0001/SM/RUS

Система менеджмента
качества сертифицирована
на соответствие требованиям
IATF 16949:2016

РОССИЙСКАЯ ФЕДЕРАЦИЯ
РЕСПУБЛИКА БАШКОРТОСТАН
АКЦИОНЕРНОЕ ОБЩЕСТВО
«САЛАВАТСТЕКЛО»
453253, РФ, РБ

г. Салават, ул. Индустриальная, 18
тел.: (3476) 33-46-25, секретарь 33-52-51
коммерческая служба 33-49-50, 33-06-63
факс (3476) 33-52-70 www.salstek.ru

ИНН 0266004050, КПП 026601001, ОКПО 04616815, ОГРН 1020201995043, р/с 40702810806404000298, Башкирское отделение № 8598 ПАО Сбербанк, БИК 048073601, к/с № 30101810300000000601



DECLARATION OF CONFORMITY

No. 012-2020/08

Unique identification code of the product-type:	Float tinted glass light green
Intended use	Buildings and construction works
Manufacturer:	“Salavatsteklo” JSC Industrialnaya str. 18, Salavat, Republic of Bashkortostan, Russia 453253
Authorised representative:	Q-GLASSTECH Sp. z o.o. ul. Pinczynska 82, 83-210 Zblewo, Polska, Phone No: +48693900319, e-mail: biuro@q-glasstech.com.pl
Harmonised standart	EN 572-9 Glass in building - Basic soda lime silicate glass products - Part 9: Evaluation of conformity/Product standard
AVCP system:	3
Notified body:	IKATES, s.r.o. - Laboratory for glass and building products testing Testing laboratory No 1139. Test report No.: 1394-CPR-157/2020

Characteristics:	3,2 mm	3,5 mm	4 mm	5 mm	6 mm
Resistance to fire	NPD	NPD	NPD	NPD	NPD
Reaction to fire	A1*	A1*	A1*	A1*	A1*
External fire performance	NPD	NPD	NPD	NPD	NPD
Bullet resistance	NPD	NPD	NPD	NPD	NPD
Explosion resistance	NPD	NPD	NPD	NPD	NPD
Burglar resistance	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials	40K				
Resistance against wind, snow, permanent load and/or imposed loads of the glass unit	45·10 ⁶ Pa				
Direct airborne sound insulation	NPD	NPD	NPD	NPD	NPD
Thermal properties	NPD	NPD	NPD	NPD	NPD
Chemical analysis	PASS	PASS	PASS	PASS	PASS
Durability	PASS	PASS	PASS	PASS	PASS
Light transmission coefficient (τ)	0,81	0,81	0,79	0,76	0,73

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Salavat
Russia
2020/08/28

Агуреев С.А. General Director of
“SAVATSTEKLO” JSC