

РЭСЭЙ ФЕДЕРАЦИЯНЫ
БАШКОРТОСТАН РЕСПУБЛИКАНЫ
“САЛАУАТ БЫЯЛА СЫҒАРЫУ”
АКЦИОНЕРЗАР ЙӘМФИӘТЕ

453253, РФ, РБ,
г. Салават, ул. Индустриальная, 18,
тел.: (3476) 33-46-25, секретарь 33-52-51,
коммерческая служба 33-49-50, 33-06-63
факс (3476) 33-52-70 www.salstek.ru

САЛАВАТСТЕКЛО



Система менеджмента
сертифицирована на соответствие
требованиям ISO 9001:2015



Система менеджмента
сертифицирована по ГОСТ Р ИСО/ТУ
16949:2009 в отношении
разработки, производства
стекла безопасного и стеклопакетов
для автомобильной промышленности

РОССИЙСКАЯ ФЕДЕРАЦИЯ
РЕСПУБЛИКА БАШКОРТОСТАН
АКЦИОНЕРНОЕ ОБЩЕСТВО
«САЛАВАТСТЕКЛО»

ИНН 0266004050 КПП 025250001
ОКПО 04616815 ОГРН 1020201995043
р/с 40702810806404000298
Башкирское отделение № 8598 ПАО Сбербанк,
БИК 048073601, к/с № 30101810300000000601

DECLARATION OF CONFORMITY

according to Annex III of the Regulation (EU) № 305/2011
Amended by Commissions delegated Regulation (EU) № 574/2014

No. 003-2017/08

1	Unique identification code of the product-type :	30
2	Name of product	Float tinted glass grey
3	Intended use:	Building and construction works
4	Manufacturer:	JSC «Salavatsteklo» Industrialnaya str, 18 Salavat, Republic of Bashkortostan Russia, 453253
5	Authorised representative:	SOKOL TRANS GROUP SP Z O.O. Polska, Lublin, 20-026, Fryderyka Chopina, 15/15A Contact person: Sokol Andriy Tel.: +38050-437-37-47 Email: sokoltransgroup@gmail.com
6	System AVCP:	System 3
7	Harmonised standard: Notified body:	EN 572-9:2004 TEST REPORT № 95A/2017 IKATES, s.r.o.- Laboratory for glass and building products testing Testing laboratory No. 1139

8. Declared performances:

Essential characteristics	Performance		
	4mm	6mm	8mm
Resistance to fire	NPD	NPD	NPD
Reaction to fire	A1*	A1*	A1*
External fire performance	NPD	NPD	NPD
Bullet resistance	NPD	NPD	NPD
Explosion resistance	NPD	NPD	NPD
Burglar resistance	NPD	NPD	NPD
Pendulum body impact resistance	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials	40K		
Resistance to snow and wind loads, continuous load and other loads	45·10 ⁶ Pa		
Direct airborne sound insulation	NPD	NPD	NPD
Thermal properties	NPD	NPD	NPD
Light transmission	0,60	0,47	0,37
Chemical analysis	PASS	PASS	PASS
Durability	PASS	PASS	PASS

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by:

General Director of JSC "Salavatsteklo"



Agureev S. A.

2017/08/17
date