САЛАВАТСТЕКЛО

РӘСӘЙ ФЕДЕРАЦИЯҺЫ
БАШКОРТОСТАН РЕСПУБЛИКАҺЫ
"САЛАУАТБЫЯЛА"
АКЦИОНЕРҘАР ЙӘМГИӘТЕ
453253, РФ, РБ
Салауат к., Индустриаль ур., 18
тел.: (3476)37-72-09, секретарь 37-71-55,
коммерция хезмәте 37-71-20,
www.salstek.ru

104213/A/0001/UK/RUS
Система менеджмента качества сертифицирована на соответствие требованиям ISO 9001:2015

104213/B/0001/SM/RUS
Система менеджмента качества сертифицирована на соответствие требованиям IATF 16949:2016

РОССИЙСКАЯ ФЕДЕРАЦИЯ
РЕСПУБЛИКА БАШКОРТОСТАН
АКЦИОНЕРНОЕ ОБЩЕСТВО
«САЛАВАТСТЕКЛО»
453253, РФ, РБ
г. Салават, ул. Индустриальная, 18
тел.: (3476) 37-72-09, секретарь 37-71-55,
коммерческая служба 37-71-20,
www.salstek.ru

ИНН 0266004050, КПП 026601001, ОКПО 04616815, ОГРН 1020201995043, р/с 40702810806404000298,Башкирское отделение №8598 ПАО Сбербанк, БИК 048073601, к/с № 30101810300000000601

DECLARATION OF CONFORMITY
No. 025-2021/11

Unique identification code of the producttype:	**Float tinted glass**	
Intended use:	Buildings and construction works	
Manufacturer	**JSC "Salavatsteklo"** **Industrialnaya str. 18, Salavat, Republic of Bashkortostan, Russia 453253**	
Harmonised standart	EN 572-9 Glass in building - Basic soda lime silicate glass products - Part 9: Evaluation of conformity/Product standard	
AVCP system:	3	
Notified body:	IKATES, s.r.o. - Laboratory for glass and building products testing Testing laboratory No 1139	
Test reports	No.: 1394-CPR-95A/2017	No 1394-CPR-157/2020

Characteristics:	**bronze**			**grey**			**ligt green**				
	4mm	**6 mm**	**8 mm**	**4mm**	**6 mm**	**8 mm**	**3,2 mm**	**3,5 mm**	**4 mm**	**5 mm**	**6 mm**
Resistance to fire	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	A1*	A1*	A1*	A1*	A1*	A1*	A1*	A1*	A1*	A1*	A1*
External fire performance	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Bullet resistance	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials	40K										
Resistance against wind, snow, permanent load and/or imposed loads of the glass unit	$45 \cdot 10^6$ Pa										
Direct airborne sound insulation	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Thermal properties	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Chemical analysis	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Durability	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Light transmission coefficient *(τv)*	0,60	0,48	0,39	0,60	0,47	0,37	0,81	0,81	0,79	0,76	0,73

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.Signed for and on behalf of the manufacturer by:

Salavat, Russia
2021/11/25

Agureev S.A.General Director of
"SAVATSTEKLO" JSC