

РӨСӘЙ ФЕДЕРАЦИЯНЫ  
БАШКОРТОСТАН РЕСПУБЛИКААНЫ  
"САЛАУАТБЫЯЛА"  
АКЦИОНЕРЗАР ЙЭМГИНӘТЕ  
453253, РФ, РБ  
Салауат к., Индустриаль ур., 18  
тел.: (3476)37-72-09, секретарь 37-71-55,  
коммерция хезмәте 37-71-20,  
www.salstek.ru

САЛАВАТСТЕКЛО



104213/A/0001/UK/RUS

Система менеджмента  
качества сертифицирована  
на соответствие требованиям  
ISO 9001:2015



104213/B/0001/SM/RUS

Система менеджмента  
качества сертифицирована  
на соответствие требованиям  
IATF 16949:2016

РОССИЙСКАЯ ФЕДЕРАЦИЯ  
РЕСПУБЛИКА БАШКОРТОСТАН  
АКЦИОНЕРНОЕ ОБЩЕСТВО  
«САЛАВАТСТЕКЛО»  
453253, РФ, РБ  
г. Салават, ул. Индустриальная, 18  
тел.: (3476) 37-72-09, секретарь 37-71-55,  
коммерческая служба 37-71-20,  
www.salstek.ru

ИНН 0266004050, КПП 026601001, ОКПО 04616815, ОГРН 1020201995043, р/с 40702810806404000298, Башкирское отделение № 8598 ПАО Сбербанк, БИК 048073601, к/с № 30101810300000000601



## DECLARATION OF CONFORMITY No. 018-2021/03

Unique identification code of the product-type:	<b>Mirror Mirroline Bronze</b>
Intended use	Buildings and construction works
Manufacturer:	<b>"Salavatsteklo" JSC</b> <b>Industrialnaya str. 18, Salavat, Republic of Bashkortostan, Russia 453253</b>
Authorised representative:	GGP Sp. z o.o Sp. k. Republic of Poland, Bialystok 15-424, ul. Lipova 33 A/1 Phone No: +48858119040; +48693900219, e-mail: <a href="mailto:biuro@gglass.pl">biuro@gglass.pl</a> SOKOL TRANS GROUP SP z o.o. 20-026, Polska, Lublin, Fryderyka Chopina 15/15A Phone No: +38 067-340-09-75 e-mail: <a href="mailto:sokoltransgroup@gmail.ru">sokoltransgroup@gmail.ru</a>
Harmonised standart	EN 1036-2 Glass in building - Mirrors from silver-coated float glass for internal use - Part 2: Evaluation of conformity - Product standard
AVCP system:	3
Notified body:	IKATES, s.r.o. - Laboratory for glass and building products testing Testing laboratory No 1139. Test report No.: 1394-CPR-156/2020

Characteristics:	
Resistance to fire	4 мм
Reaction to fire	NPD
External fire performance	A1*
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	NPD
Resistance against sudden temperature changes and temperature differentials	40K
Resistance against wind, snow, permanent load and/or imposed loadsof the glass unit	NPD
Direct airborne sound insulation	NPD
Thermal properties	NPD
Condensation water test an constant temperature in atmosphere with	PASS
Copper accelerated asid salt spray (CASS)	PASS
Varnish adhesion	PASS
Light reflection (pv)	0,39

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Salavat  
Russia  
2021/03/26



Agureev S.A. General Director of  
"SALAVATSTEKLO" JSC