



РӨСӘЙ ФЕДЕРАЦИЯҒЫ
БАШКОРТОСТАН РЕСПУБЛИКАҒЫ
“САЛАУАТБЫЯЛА”
АКЦИОНЕРҒАР ЙӘМҒИӘТЕ
453253, РФ, РБ
Салауат к., Индустриаль ур., 18
тел.: (3476)33-46-25, секретарь 33-52-51
коммерция хезмәте 33-49-50, 33-06-63
факс (3476) 33-52-70 www.salstek.ru



104213/A/0001/UK/RUS
Система менеджмента
качества сертифицирована
на соответствие требованиям
ISO 9001:2015



104213/B/0001/SM/RUS
Система менеджмента
качества сертифицирована
на соответствие требованиям
IATF 16949:2016

РОССИЙСКАЯ ФЕДЕРАЦИЯ
РЕСПУБЛИКА БАШКОРТОСТАН
АКЦИОНЕРНОЕ ОБЩЕСТВО
«САЛАВАТСТЕКЛО»
453253, РФ, РБ
г. Салават, ул. Индустриальная, 18
тел.: (3476) 33-46-25, секретарь 33-52-51
коммерческая служба 33-49-50, 33-06-63
факс (3476) 33-52-70 www.salstek.ru

ИНН 0266004050, КПП 026601001, ОКПО 04616815, ОГРН 1020201995043, р/с 40702810806404000298, Башкирское отделение № 8598 ЦАО Сбербанк, БИК 048073601, к/с № 30101810300000000601



DECLARATION OF CONFORMITY No. 015-2020/08

Unique identification code of the product-type:	Mirror Mirroline Bronze
Intended use	Buildings and construction works
Manufacturer:	“Salavatsteklo” JSC Industrialnaya str. 18, Salavat, Republic of Bashkortostan, Russia 453253
Authorised representative:	GGP Sp. z o.o Sp. k. Republic of Poland, Bialystok 15-424, ul. Lipova 33 A/1 Phone No: +48858119040; +48693900219, e-mail: biuro@gglass.pl
Harmonised standart	EN 1036-2 Glass in building - Mirrors from silver-coated float glass for internal use - Part 2: Evaluation of conformity - Product standard
AVCP system:	3
Notified body:	IKATES, s.r.o. - Laboratory for glass and building products testing Testing laboratory No 1139. Test report No.: 1394-CPR-156/2020

Characteristics:	
Resistance to fire	4 мм
Reaction to fire	NPD
External fire performance	AI*
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	NPD
Resistance against sudden temperature changes and temperature differentials	40K
Resistance against wind, snow, permanent load and/or imposed loadsof the glass unit	NPD
Direct airborne sound insulation	NPD
Thermal properties	NPD
Condensation water test an constant temperature in atmosphere with	PASS
Copper accelerated asid salt spray (CASS)	PASS
Varnish adhesion	PASS
Light reflection (pv)	0,43

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Salavat
Russia
2020/08/28



Agureev S.A. General Director of
“SALAVATSTEKLO” JSC