

РӨСӘЙ ФЕДЕРАЦИЯҢЫ
БАШКОРТОСТАН РЕСПУБЛИКАҢЫ
"САЛАУАТБЫЯЛА"
АКЦИОНЕРЗАР ЙӘМҒИНӘТЕ
453253, РФ, РБ
Салауат к. Индустриаль ур., 18
тел.: (3476)37-72-09, секретарь 37-71-55,
коммерция хезмәте 37-71-20,
www.salstek.ru

САЛАВАТСТЕКЛО



104213/A/0001/UK/RUS

Система менеджмента
качества сертифицирована
на соответствие требованиям
ISO 9001:2015



104213/B/0001/SM/RUS

Система менеджмента
качества сертифицирована
на соответствие требованиям
IATF 16949:2016

РОССИЙСКАЯ ФЕДЕРАЦИЯ
РЕСПУБЛИКА БАШКОРТОСТАН
АКЦИОНЕРНОЕ ОБЩЕСТВО
«САЛАВАТСТЕКЛО»
453253, РФ, РБ
г. Салават, ул. Индустриальная, 18
тел.: (3476) 37-72-09, секретарь 37-71-55,
коммерческая служба 37-71-20,
www.salstek.ru

ИНН 0266004050, КПП 026601001, ОКПО 04616815, ОГРН 1020201995043, р/с 40702810806404000298, Башкирское отделение № 8598 ПАО Сбербанк, БИК 048073601, к/с № 30101810300000000601



DECLARATION OF CONFORMITY No. 024-2021/11

| | |
|---|---|
| Unique identification code of the product-type: | Float glass clear |
| Intended use | Buildings and construction works |
| Manufacturer: | “Salavatsteklo” JSC Industrialnaya str. 18, Salavat, Republic of Bashkortostan, Russia 453253 |
| Harmonised standart | EN 572-9 Glass in building - Basic soda lime silicate glass products- Part 9 Evaluation of conformity/Product standard |
| AVCP system: | 3 |
| Notified body: | IKATES, s.r.o. - Laboratory for glass and building products testing Testing laboratory No 1139. Test report No.: 1394-CPR-95A/2017 |

| Characteristics: | 1,8 mm | 2,0 mm | 3,0 mm | 4,0 mm | 5,0 mm | 6,0 mm | 8,0 mm | 10,0 mm | 12,0 mm |
|---|-----------------------|--------|--------|--------|--------|--------|--------|---------|---------|
| Resistance to fire | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD |
| Reaction to fire | A1* | A1* | A1 * | A1 * | A1 * | A1 * | A1 * | A1 * | A1 * |
| External fire performance | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD |
| Bullet resistance | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD |
| Explosion resistance | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD |
| Burglar resistance | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD |
| Pendulum body impact resistance | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD |
| Resistance against sudden temperature changes and temperature differentials | 40K | | | | | | | | |
| Resistance to snow and wind loads, continuous load and other loads | 45·10 ⁶ Pa | | | | | | | | |
| Direct airborne sound insulation | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD |
| Thermal properties | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD | NPD |
| Durability | PASS | PASS | PASS | PASS | PASS | PASS | PASS | PASS | PASS |
| Chemical analysis | PASS | PASS | PASS | PASS | PASS | PASS | PASS | PASS | PASS |
| Radiation properties: | | | | | | | | | |
| Light transmission (τ _v) | 0,91 | 0,91 | 0,90 | 0,90 | 0,90 | 0,89 | 0,88 | 0,87 | 0,86 |

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Salavat, Russia
2021/11/25

Agureev S.A. General Director of
“SALAVATSTEKLO” JSC